



# PARKER PUMP LTD



626 Bearing 2D drawings and 3D CAD models

## TIMKEN 626 Single Row Ball Bearings

Bearing No. 626

|                                 |   |
|---------------------------------|---|
| Category                        | Single Row Ball Bearings                                  |
| Inventory                       | 0.0   |
| Manufacturer Name               | TIMKEN  |
| Minimum Buy Quantity            | N/A   |
| Weight                          | 0   |
| EAN                             | 0053893772592   |
| Product Group                   | B00308  |
| Enclosure                       | Open  |
| Precision Class                 | ABEC 1   ISO P0   |
| Maximum Capacity / Filling Slot | No  |
| Rolling Element                 | Ball Bearing  |
| Snap Ring                       | No  |
| Internal Special Features       | No  |
| Cage Material                   | Steel   |
| Internal Clearance              | C0-Medium   |
| Inch - Metric                   | Metric  |
| Category                        | Single Row Ball Bearing                                   |
| UNSPSC                          | 31171504  |
| Harmonized Tariff Code          | 8482.10.50.68   |
| Noun                            | Bearing   |
| Keyword String                  | Ball  |
| Manufacturer URL                | <a href="http://www.timken.com">http://www.timken.com</a> |
| Weight / LBS                    | 0.017   |
| d                               | 0.236 Inch   6 Millimeter                                 |
| Outer Race Width                | 0.236 Inch   6 Millimeter                                 |
| Inner Race Width                | 0.236 Inch   6 Millimeter                                 |



## PARKER PUMP LTD

|                          |                            |
|--------------------------|----------------------------|
| D                        | 0.748 Inch   19 Millimeter |
| Bore Size d              | 6 mm                       |
| Features                 | Open                       |
| Weight                   | 0.0070 Kg                  |
| Outside Diameter D       | 19.0000 mm                 |
| Outside Ring Width B     | 6.000 mm                   |
| Radius Rs min            | 0.300 mm                   |
| Cr - Dynamic Load Rating | 2.3 kN                     |
| C0r - Static Load Rating | 0.89 kN                    |
| Grease Limiting Speed    | 38000 rpm                  |
| Oil Limiting Speed       | 45000 rpm                  |